



iSXblue II+ GPS



iSXblue II+ GNSS



SXblue Platinum



SXblue Platinum AG

Description	Submeter	Submeter GNSS	Submeter/dm/cm Atlas/RTK	
Supported GNSS Signals	GPS	GPS/GLONASS/BeiDou/Galileo/QZSS		
GNSS Systems Used	1	All in view		
GNSS Frequency Tracking	L1		L1/L2/L5	
Channels	162		372	
SBAS Accuracy	30 - 60 cm			
L-BAND			Atlas: H10/H30/Basic(H50)	
RTK Accuracy HOR.RMS	10 mm + 1 ppm		8 mm + 1 ppm	
Integrated Bluetooth	✓	✓	✓	✓
iPhone/iPad	✓	✓	✓	
Android/Windows	✓	✓	✓	✓
USB Port	✓	✓	✓	
Serial Port RS-232	✓	✓	✓	✓
Update Rate	1 Hz standard 10 Hz - 20 Hz option		1 Hz standard 10 Hz - 20 Hz - 50 Hz option	
Battery Life	> 15 hours	> 14 hours	> 12 hours	External Power 6 V to 30 V
Battery Capacity	6000 mAh 7.2 V			

Sxblue

DATA COLLECTORS



SXPad 200



SXPad 1000P



SXPad 1500



SXPro GNSS

Operating System	Windows® Mobile 6.5 Pro			
CPU	806 MHz	1 GHz	1 GHz	1 GHz
Memory	512 MB RAM / 4 GB Flash Expandable with TF card	512 MB RAM / 8 GB Flash Expandable with TF card	512 MB RAM / 1 GB Flash Included 16 GB TF card	512 MB RAM / 1 GB SSD Included 4 GB TF card
Display	3.7" VGA		5" TFT LCD	3.7" VGA
Camera	5 MP			
Wi-Fi	✓	✓	✓	✓
Integrated Bluetooth	✓	✓	Long Range Bluetooth (optional)	✓
Cellular Modem	✓	✓	✓	✓
Supported GNSS Signals	GPS / L1	GNSS / L1	GNSS / L1	GPS/GLONASS/ BeiDou /L1
GPS Accuracy	2.5 meters	1 - 3 meters		30 - 60 cm (SBAS)
IP rating	IP65	IP67	IP67	IP65
Battery Life	10 hours		> 6 hours	> 10 hours

Authorized Distributor

© Copyright January 20320, Geneq inc. All rights reserved.
Specifications subject to change without notice. The Bluetooth™
trademarks are owned by Bluetooth SIG, Inc, U.S.A.

INFO@SXBLUEGPS.COM 514 354-2511 1 800 463-4363 WWW.SXBLUEGPS.COM